

MIRA EXTRA BSM

Part Number: BSM: 1.0.122.25.2



THE SHOWER THAT'S A LITTLE ALTERNATIVE

FOR CUSTOMERS WHO WANT THERMOSTATIC CONTROL FOR BOTH SHOWER AND BATH FILL SEE PAGE 57



TEMPERATURE CONTROL

Thermostatic temperature stability (shower only)

EASY TO FIT

Fits onto standard bath tap holes

EASY TO SERVICE

Replaceable cartridge with integral filters

FOR YOUR CUSTOMER

One control for on/off and temperature

Conventional non-thermostatic bath fill

A convenient, alternative way of showering

4 spray showerhead with rub clean rubber nozzles

TECH DETAILS

TEMPERATURE CONTROL

Control type: Thermostatic Shower Control

INSTALLATION

Water entry points: Rising only

Inlet connections: 3/4" BSP Male

Outlet connections: 1/2" BSP Male

Reversed inlets supported: No

SUPPLY CONDITIONS (hot and cold supplies to be at nominally equal pressure)

Cold water range: Up to 25°C

Hot water range: 50°C-85°C (operating)
55°C-65°C (recommended)

Minimum maintained pressure: 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

PERFORMANCE

Flow rate (at handset): 15 l/min

Temperature stability: $\pm 2^\circ\text{C}$

SAFETY FEATURES

Automatic shutdown: Yes – shower only

Factory set to safe max temp: Factory set to 42°C

Adjustable maximum temperature for on-site conditions

ACCESSORIES

Wide range of accessories available at www.mirashowers-store.co.uk

TECH DRAWINGS

